

QSCD-CERTIFICATE

PURSUANT TO ART. 30 PARA. 3 LIT. B eIDAS¹

Qualified Signature and Seal Creation Device (QSCD)

Intesi PkBox, version 3.4

Applicant:
Intesi Group S.p.A.
Via Torino 48
20123 Milano
Italy

Reference number: A-SIT-VIG-25-036

QSCD-Certificate valid from:
See Date of Qualified Electronic Signature

1. Product Description

PkBox is a product for electronic signatures and seals intended to be used as a Qualified Remote Signature and Seal Creation Device (QSCD) in a secure operational environment. It implements a Trustworthy System Supporting Server Signing (TW4S) in accordance with EN 419 241-1:2018 and EN 419 241-2:2019. When used in combination with qualified certificates PkBox generates qualified electronic signatures and seals as defined in Regulation (EU) No. 910/2014 (eIDAS) with the legal effects defined within.

Subcomponents:

An HSM (Hardware Security Module) device² (nCipher nShield Solo XC/Connect XC or Entrust nShield5s/nShield5c³) is used as a cryptographic module for the generation and protection of the signature and seal creation data (SCD). The HSM is operated according to its respective FIPS⁴ 140-2 level 3, FIPS 140-3 level 3 or Common Criteria certification.

¹ Regulation (EU) No 910/2014 of the European Parliament and of the Council of 23 July 2014, on electronic identification and trust services for electronic transactions in the internal market and repealing Directive 1999/93/EC amended by Regulation (EU) 2024/1183 of the European Parliament and of the Council of 11 April 2024

² The certified hardware and firmware versions of the used cryptographic modules, for which this QSCD certificate is valid, are given in Section 6.

³ Manufacturer: Entrust, One Station Square, Cambridge CB1 2GA, United Kingdom

⁴ FIPS – Federal Information Processing Standard

The HSM device is accessed only through PkBox COD (“Credential On Database”) which uses a secure mechanism provided by the HSM for storing private keys outside the HSM in a database. The PkBox COD module is also responsible for the validation of the one-time-password (OTP) to ensure that the SCD can be reliably protected by the legitimate signatory against the use of others.

The Signature Creation Application (SCA) sends the entire document to be signed either directly to PkBox COD or uses a PkBox Remote module that is installed in the same IT infrastructure with the SCA. PkBox Remote is then responsible for the hash computation and sends the document hash to PkBox COD. Both PkBox modules guarantee the document integrity during the signature process, by verifying the signed hash against the calculated hash value. As an alternative procedure, the SCA sends the document hash to PkBox COD or PkBox Remote and PkBox modules return the signed hash value. In this scenario, the document integrity is verified and guaranteed by the SCA.

The SCA and the PkBox Remote module are not part of the QSCD and thus outside of the scope of this certification.

Generation of Signature and Seal Creation Data:

The registration takes place either directly via the TSP (Trust Service Provider) or by means of delegated authentication with trustworthy third parties – e.g., identity providers, registration authorities. The SCD/SVD key pair is generated within the HSM. During the enrolment process the signatory has to define a secret PIN⁵. To provide strong authentication a one-time-password (OTP) mechanism is used in addition to this PIN. PkBox can be configured to address different OTP providers, for example:

- Vasco Vacman controller engine
- Vasco IdentiKey Server
- RSA SecureID Authentication
- RSA SecureID ACE Server
- Radius server together with: Vasco, RSA, SafeNet or McAfee validation server
- Time4ID SMS and Mobile Token OTP Engine
- Time4ID OATH Engine together with Intesi Group virtual tokens and Gemalto OTP devices
- CA Strong Authentication VAS using remote CA Technologies server with a variety of authentication devices
- Asseco Aseba SxS OTP Solution VAS using remote Asseco server with a variety of authentication devices
- Gemalto Authentication Server using remote Gemalto server

PkBox can also be configured to address further OTP providers, not listed herein but having the same level of trustworthiness, provided that the conditions in section 4 are fulfilled.

The remote signature or seal mechanism can also use an alternative two-factor authentication method, in which the authentication of the two factors is split between the SCA and PkBox COD (delegated authentication). In this case the PIN value is not provided by the signatory but it is a derived PIN provided by the SCA to the TOE⁶ after a successful user authentication. This method is only available, if the SCA is held by a trustworthy entity, which is audited by the QTSP (Qualified Trust Service Provider) operating the QSCD.

After SCD generation a certificate request (PKCS#10) is generated and transmitted to a certificate authority. The process of issuing qualified certificates is outside the scope of this certification.

Storage of Signature and Seal Creation Data:

The QSCD supports long-term signatures and seals based on qualified certificates that are stored persistently. However, the QSCD does not support short-term (also known as “one-time”) signatures

⁵ PIN – Personal Identification Number

⁶ TOE – Target of Evaluation

and seals based on qualified certificates, where SCD are immediately destroyed after the signature or seal creation. Therefore, the SCD are stored in encrypted form in a database outside of the HSM.

The OTP provider and the OTP identifier are stored together with the encrypted SCD in the database. All cryptographic operations of generation, encryption and decryption of SCD are implemented within the HSM. The usage of SCD within the HSM is only possible after a successful OTP validation and authentication with the signatory's secret PIN.

Signature and Seal Creation:

PkBox's signature or seal process is structured as follows:

- The signature or seal credential specified by the signatory or creator of the seal is received from the credential database.
- The associated SCD is imported into the HSM.
- The PIN provided by the signatory or creator of the seal, or the derived PIN provided by the SCA in the case of delegated authentication, is verified inside the HSM.
- The selected credential access policies are verified.
- The validity of the OTP is checked using the vendor defined within the credential access policies. In case of a failure in the verification of PIN or OTP values, the signing or sealing process is aborted.
- In case of a successful verification of all the authentication parameters, the signature or seal is generated within the HSM.

2. Compliance with the Requirements of eIDAS

The QSCD meets the following requirements, provided that the conditions in section 4 are fulfilled:

- requirements laid down in Article 29 para 1⁷ eIDAS,
- requirements laid down in Article 39 para 1⁸ eIDAS,
- requirements laid down in Annex II eIDAS (para 1 lit. a⁹, b¹⁰, c¹¹, d¹², para 2¹³, para 3¹⁴, para 4 lit a¹⁵, b¹⁶)

⁷ Qualified electronic signature creation devices shall meet the requirements laid down in Annex II.

⁸ Article 29 shall apply mutatis mutandis to requirements for qualified electronic seal creation devices.

⁹ Qualified electronic signature creation devices shall ensure, by appropriate technical and procedural means, that the confidentiality of the electronic signature creation data used for electronic signature creation is reasonably assured.

¹⁰ Qualified electronic signature creation devices shall ensure, by appropriate technical and procedural means, that the electronic signature creation data used for electronic signature creation can practically occur only once.

¹¹ Qualified electronic signature creation devices shall ensure, by appropriate technical and procedural means, that the electronic signature creation data used for electronic signature creation cannot, with reasonable assurance, be derived and the electronic signature is reliably protected against forgery using currently available technology.

¹² Qualified electronic signature creation devices shall ensure, by appropriate technical and procedural means, that the electronic signature creation data used for electronic signature creation can be reliably protected by the legitimate signatory against use by others.

¹³ Qualified electronic signature creation devices shall not alter the data to be signed or prevent such data from being presented to the signatory prior to signing.

¹⁴ Generating or managing electronic signature creation data on behalf of the signatory may only be done by a qualified trust service provider.

¹⁵ Without prejudice to point (d) of point 1, qualified trust service providers managing electronic signature creation data on behalf of the signatory may duplicate the electronic signature creation data only for back-up purposes provided the following requirements are met: the security of the duplicated datasets must be at the same level as for the original datasets.

¹⁶ Without prejudice to point (d) of point 1, qualified trust service providers managing electronic signature creation data on behalf of the signatory may duplicate the electronic signature creation data only for back-

The compliance of the QSCD is thus confirmed within the following categories:

- components and procedures for the generation of signature or seal creation data,
- components and procedures for the storage of signature or seal creation data,
- components and procedures for the processing of signature or seal creation data

3. Validity Period of the QSCD-Certificate

This QSCD-Certificate is valid up to 5 years or up to a preceding revocation by A-SIT.

On assignment A-SIT will conduct a continuous surveillance concerning the security of the technical components and processes used as well as the suitability of the cryptographic algorithms and parameters. The issuance of this QSCD-Certificate includes surveillance for a period of two years. In order to maintain a valid certification, the applicant has to conduct a vulnerability assessment every two years and remedy any identified vulnerabilities in a timely manner. The QSCD-Certificate will be revoked if the technical components and processes or the cryptographic algorithms and parameters used no longer reflect the state of the art, if vulnerability assessments are not conducted every two years, if identified vulnerabilities are not remedied in a timely manner or if there is no further surveillance assigned.

4. Operating Conditions

The validity of this QSCD-Certificate is subject to the conditions stated below. The measures taken shall be

- ascertained by the trust service provider's security and certification policy,
 - integrated into the guidance of the signatory or creator of a seal and
 - their effect shall be ensured by means of supervision (in accordance with Article 20 eIDAS).
- (1) The unambiguous assignment and the safe completion of the user session, the confidentiality and integrity of the authorization codes as well as the integrity of the data to be signed or to be sealed during transmission from the signatory or creator of a seal to the QSCD are part of the QSCD's system environment¹⁷ and thus outside the scope of this QSCD-certificate. It must be ensured that the signatories or creators of a seal are informed that components used for the initiation of the signature or sealing process (OTP device, mobile phone, web browser) must be suitably protected. The signatories shall keep control of their assigned OTP devices and shall promptly report any circumstance where the credential is compromised according to the defined revocation or suspension procedures.
 - (2) The QSCD must be operated by a qualified trust service provider.
 - (3) In case of delegated authentication, the QTSP deploying PkBox COD shall ensure that the party deploying the SCA to which the authentication is delegated uses authentication means and mechanisms that meet the requirements specified in EC Implementing Regulation 2015/1502 for assurance level substantial or higher¹⁸. The SCA shall not cache the derived PIN obtained by PkBox COD for a signature operation for longer than necessary to complete the respective transaction.

up purposes provided the following requirements are met: the number of duplicated datasets shall not exceed the minimum needed to ensure continuity of the service.

¹⁷ in accordance with recital 56 of eIDAS

¹⁸ COMMISSION IMPLEMENTING REGULATION (EU) 2015/1502 of 8 September 2015 on setting out minimum technical specifications and procedures for assurance levels for electronic identification means pursuant to Article 8(3) of Regulation (EU) No 910/2014 of the European Parliament and of the Council on electronic identification and trust services for electronic transactions in the internal market; as defined in ANNEX Clauses 2.1, 2.2.1 and 2.3.1

- (4) The qualified trust service provider must operate the QSCD in a protected environment, in particular it must be ensured that:
- physical access to the QSCD is limited to authorized privileged users, the QSCD shall be installed in a secured and controlled access area of the IT department of the organization, no one but the appliance administrator shall be able to physically access the appliance or its surroundings
 - the QSCD or any of its externally stored assets are protected against loss or theft
 - the QSCD is regularly inspected to deter and detect tampering (including attempts to access side-channels, or to access connections between physically separate parts of the QSCD, or parts of the hardware appliance); the appliance administrator must periodically check the appliance's case for any evidence of physical tampering, the check must be performed at least daily, alternatively a remote continuous monitoring and surveillance system (RCMSS)¹⁹ can be set up; in case of any evidence of physical tampering the HSM shall be disconnected and reinitialized
 - the QSCD is protected against the possibility of attacks based on emanations (e.g., electromagnetic emanations) according to risks assessed for the operating environment
 - the QSCD is protected against unauthorized software and configuration changes; the appliance administrator must periodically check that the secure environment of the QSCD is not compromised with any hardware or software that can violate the security of the QSCD; this includes network sniffers and devices that may be used for timing attacks. This check must be performed at least daily or alternatively – if the RCMSS is available – when a security alert is received
 - all instances of the QSCD holding the same assets (e.g., where a key is present as a backup in more than one instance of the QSCD) are protected to an equivalent level
- (5) The HSMs must be initialised and operated according to their respective certification.
- (6) During HSM initialisation a quorum of at least two has to be defined for the HSM's Administrator Card Set (ACS) and the generated smart cards have to be controlled by different persons to ensure the principle of dual control.
- (7) Electronic signature or seal creation data may be duplicated for back-up purposes only to the extent strictly necessary to ensure continuity of the service.
- (8) Only those cryptographic algorithms, parameters and hash functions listed in section five shall be used for the creation of qualified electronic signatures or qualified electronic seals.
- (9) External authentication mechanisms, which are used to authenticate a user in order to create a qualified electronic signature or seal, shall correspond to an authentication means equivalent to EC Implementing Regulation 2015/1502 for assurance level substantial or higher ²⁰.
- (10) It must be ensured that components of signers, which have vulnerabilities or are otherwise not suitable for authentication, cannot be used to authorize a signature or seal creation.
- (11) The qualified trust service provider operating the QSCD must ensure that RSA keys with a key size lower than 3000-bit cannot be used for the creation of qualified electronic signatures or qualified electronic seals after 2025-12-31.
- (12) Qualified trust service providers issuing qualified certificates based on keys generated by the QSCD must ensure that qualified certificates based on RSA keys with a key size lower than 3000-bit are not valid beyond 2025-12-31.

¹⁹ Defined in PkBox RCMSS Based Procedure version 1.0. In this case a physical check on-premise is required only when a security alert has been triggered by the monitoring and surveillance system.

²⁰ COMMISSION IMPLEMENTING REGULATION (EU) 2015/1502 of 8 September 2015 on setting out minimum technical specifications and procedures for assurance levels for electronic identification means pursuant to Article 8(3) of Regulation (EU) No 910/2014 of the European Parliament and of the Council on electronic identification and trust services for electronic transactions in the internal market; as defined in ANNEX Clauses 2.1, 2.2.1 and 2.3.1

5. Algorithms and Corresponding Parameters

For the creation of qualified electronic signatures or qualified electronic seals the QSCD uses the cryptographic algorithms:

- RSASSA²¹-PKCS1-v1_5 or RSASSA-PSS²² according to PKCS#1 v2.2 (IETF RFC 8017) and a modulus length of 2048 bits until 31.12.2025 at the latest.
- RSASSA-PKCS1-v1_5 or RSASSA-PSS according to PKCS#1 v2.2 (IETF RFC 8017) and modulus lengths of 3072 or 4096 bits.
- ECDSA²³ with the following curves defined in NIST²⁴ FIPS PUB 186-4: P-256, P-384, P-521, K-283, B-283, K-409, B-409, K-571, B-571.

For the calculation of hash values the following algorithms are supported²⁵:

- SHA²⁶-256, SHA-384 and SHA-512 according to FIPS PUB 180-4

6. Assurance Level and Strength of Mechanism

For the supported HSM types nCipher nShield Solo XC and nShield Connect XC, with firmware versions 12.50.11, 12.72.1, and 12.72.3, the following FIPS 140-2 level 3 certifications apply:

- FIPS validation certificate No. 3760 – issued on 2020-12-09 and last updated on 2022-02-18 by the US (National Institute of Standards and Technology) and the Canadian (Canadian Centre for Cyber Security) FIPS 140-2 certification body for the firmware version 12.50.11 and hardware versions NC4035E-000 and NC4335N-000, Build Standard A
- FIPS validation certificate No. 4335 – issued on 2022-10-16 and last updated on 2024-06-18 by the US (National Institute of Standards and Technology) and the Canadian (Canadian Centre for Cyber Security) FIPS 140-2 certification body for the firmware versions 12.72.1 and 12.72.3 and hardware versions nC4035E-000 and nC4335N-000, Build Standard A

The certificates confirm that the respective HSM was successfully evaluated against FIPS 140-2 level 3.

For the supported HSM types nCipher nShield Solo XC and nShield Connect XC, with firmware version 12.60.15, the Common Criteria certificate CC-21-0368256, issued on 2021-03-17 by TÜV Rheinland Nederland B.V., applies. The certificate confirms that the respective HSM was successfully evaluated against Common Criteria version 3.1 revision 5, EAL4+²⁷ (augmented with ALC_FLR.2²⁸ and AVA_VAN.5²⁹).

For the supported HSM types Entrust nShield5s and nShield5c, with firmware version 13.4.5, the following FIPS 140-3 level 3 certification applies:

- FIPS validation certificate No. 4765 – issued on 2024-08-19 and last updated on 2025-04-01 by the US (National Institute of Standards and Technology) and the Canadian (Canadian Centre for Cyber Security) FIPS 140 Series certification body for the firmware version 13.4.5 and hardware versions PCA10005-01 revision 03 and 04

²¹ RSASSA – RSA Signature Scheme with Appendix (RSA – Rivest, Shamir, Adleman)

²² PSS – Probabilistic Signature Scheme

²³ ECDSA – Elliptic Curve Digital Signature Algorithm

²⁴ NIST – National Institute of Standards and Technology

²⁵ Hash value calculation may also be performed outside of the QSCD (either by the SCA or – in the case of PKBox Remote configuration – by the PKBox Remote Module)

²⁶ SHA – Secure Hash Algorithm

²⁷ EAL – Evaluation Assurance Level

²⁸ Life-Cycle Support – Flaw reporting procedures

²⁹ Vulnerability Assessment – Advanced methodical vulnerability analysis

The certificate confirms that the respective HSM was successfully evaluated against FIPS 140-3 level 3.

For the supported HSM types Entrust nShield5s and nShield5c, with firmware version 13.5.1, the Common Criteria certificate NSCIB-CC-2200057-01, issued on 2024-04-11 by TrustCB B.V., applies. The certificate confirms that the respective HSM was successfully evaluated against Common Criteria version 3.1 revision 5, EAL4+ (augmented with ALC_FLR.2²⁸ and AVA_VAN.5²⁹).

Since there are no standards for the security assessment published by the European Commission by means of implementing acts, the QSCD certification was performed under eIDAS article 30 para. 3 lit. b and the confirmation body applied equivalent security levels taking into account the state of the art.

In its intended environment the QSCD resists against attackers with high attack potential.

The results of the performed assessment which is the basis for this QSCD-Certificate are documented in the QSCD-Certification report under the reference A-SIT-VIG-25-036.

Authorized Signature:

A-SIT Secure Information Technology Center – Austria

Vienna, (Date see electronic signature)



**placeholder for the
electronic signature**
NR: 1

Herbert Leitold, Director